


## Low-power quad operational amplifiers

Datasheet - production data

**Description**

This circuit consists of four independent, high-gain operational amplifiers (op amps) which employ internal frequency compensation and are specifically designed for automotive and industrial control systems.

The device operates from a single power supply over a wide range of voltages. Operation from split power supplies is also possible and the low-power supply current drain is independent from the power supply voltage magnitude.

**Features**


- Wide gain bandwidth: 1.3 MHz
- Input common-mode voltage range includes negative rail
- Large voltage gain: 100 dB
- Supply current per amplifier: 375  $\mu$ A
- Low input bias current: 20 nA
- Low input offset current: 2 nA
- Wide power supply range:
  - Single supply: 3 V to 30 V
  - Dual supplies:  $\pm 1.5$  V to  $\pm 15$  V

## Contents

|          |                                                                |           |
|----------|----------------------------------------------------------------|-----------|
| <b>1</b> | <b>Schematic diagram.....</b>                                  | <b>3</b>  |
| <b>2</b> | <b>Pinout information.....</b>                                 | <b>4</b>  |
| <b>3</b> | <b>Absolute maximum ratings and operating conditions .....</b> | <b>5</b>  |
| <b>4</b> | <b>Electrical characteristics .....</b>                        | <b>7</b>  |
| <b>5</b> | <b>Electrical characteristic curves .....</b>                  | <b>9</b>  |
| <b>6</b> | <b>Typical single-supply applications .....</b>                | <b>12</b> |
| <b>7</b> | <b>Package information .....</b>                               | <b>14</b> |
| 7.1      | SO14 package information.....                                  | 15        |
| 7.2      | TSSOP14 package information.....                               | 16        |
| 7.3      | QFN16 3x3 package information.....                             | 17        |
| <b>8</b> | <b>Ordering information.....</b>                               | <b>19</b> |
| <b>9</b> | <b>Revision history .....</b>                                  | <b>20</b> |


# 1 Schematic diagram

Figure 1: Schematic diagram (1/4 LM2902)



## 2 Pinout information

Figure 2: Package pin connections (top view)



1. The exposed pads of the QFN16 3x3 can be connected to VCC- or left floating.

### 3 Absolute maximum ratings and operating conditions

Table 1: Absolute maximum ratings (AMR)

| Symbol            | Parameter                                                                      | Value                                               | Unit  |
|-------------------|--------------------------------------------------------------------------------|-----------------------------------------------------|-------|
| V <sub>CC</sub>   | Supply voltage <sup>(1)</sup>                                                  | ± 16 to 32                                          | V     |
| V <sub>id</sub>   | Differential input voltage <sup>(2)</sup>                                      | 32                                                  |       |
| V <sub>in</sub>   | Input voltage                                                                  | -0.3 to 32                                          |       |
|                   | Output short-circuit duration <sup>(3)</sup>                                   | Infinite                                            | s     |
| T <sub>j</sub>    | Maximum junction temperature                                                   | 150                                                 | ° C   |
| T <sub>stg</sub>  | Storage temperature range                                                      | -65 to 150                                          |       |
| I <sub>in</sub>   | Input current : V <sub>in</sub> driven negative <sup>(4)</sup>                 | 5 in DC or 50 in AC<br>(duty cycle = 10 %, T = 1 s) | mA    |
|                   | Input current : V <sub>in</sub> driven positive above AMR value <sup>(5)</sup> | 0.4                                                 |       |
| R <sub>thja</sub> | Thermal resistance junction-to-ambient <sup>(6)</sup>                          | SO14                                                | ° C/W |
|                   |                                                                                | TSSOP14                                             |       |
|                   |                                                                                | QFN16 3x3                                           |       |
| R <sub>thjc</sub> | Thermal resistance junction-to-case                                            | SO14                                                |       |
|                   |                                                                                | TSSOP14                                             |       |
|                   |                                                                                | QFN16 3x3                                           |       |
| ESD               | HBM: human body model <sup>(7)</sup>                                           | 370                                                 | V     |
|                   | MM: machine model <sup>(8)</sup>                                               | 150                                                 |       |
|                   | CDM: charged device model <sup>(9)</sup>                                       | 1500                                                |       |

#### Notes:

<sup>(1)</sup>All voltage values, except the differential voltage are with respect to the network ground terminal.

<sup>(2)</sup>Differential voltages are the non-inverting input terminal with respect to the inverting input terminal.

<sup>(3)</sup>Short-circuits from the output to V<sub>CC</sub><sup>+</sup> can cause excessive heating and eventual destruction. The maximum output current is approximately 20 mA, independent of the magnitude of V<sub>CC</sub><sup>+</sup>.

<sup>(4)</sup>This input current only exists when the voltage at any of the input leads is driven negative. It is due to the collector-base junction of the input PNP transistor becoming forward-biased and thereby acting as an input diode clamp. In addition to this diode action, there is an NPN parasitic action on the IC chip. This transistor action can cause the output voltages of the op amps to go to the V<sub>CC</sub> voltage level (or to ground for a large overdrive) for the time during which an input is driven negative. This is not destructive and normal output is restored for input voltages above -0.3 V.

<sup>(5)</sup>The junction base/substrate of the input PNP transistor polarized in reverse must be protected by a resistor in series with the inputs to limit the input current to 400 μA max (R = (V<sub>in</sub> - 36 V)/400 μA).

<sup>(6)</sup>R<sub>thja/c</sub> are typical values.

<sup>(7)</sup>Human body model: a 100 pF capacitor is charged to the specified voltage, then discharged through a 1.5 kΩ resistor between two pins of the device. This is done for all couples of connected pin combinations while the other pins are floating.

<sup>(8)</sup>Machine model: a 200 pF capacitor is charged to the specified voltage, then discharged directly between two pins of the device with no external series resistor (internal resistor < 5 Ω). This is done for all couples of connected pin combinations while the other pins are floating.

<sup>(9)</sup>Charged device model: all pins and the package are charged together to the specified voltage and then discharged directly to the ground through only one pin. This is done for all pins.

**Table 2: Operating conditions**

| Symbol            | Parameter                            |                                                        | Value                                 | Unit |
|-------------------|--------------------------------------|--------------------------------------------------------|---------------------------------------|------|
| V <sub>CC</sub>   | Supply voltage                       |                                                        | 3 to 30                               | V    |
| V <sub>ICM</sub>  | Common mode input voltage range      |                                                        | (V <sub>CC</sub> <sup>+</sup> ) - 1.5 |      |
|                   |                                      | T <sub>min</sub> ≤ T <sub>amb</sub> ≤ T <sub>max</sub> | (V <sub>CC</sub> <sup>+</sup> ) - 2   |      |
| T <sub>oper</sub> | Operating free-air temperature range |                                                        | -40 to 125                            | ° C  |

## 4 Electrical characteristics

Table 3:  $V_{CC+} = 5\text{ V}$ ,  $V_{CC-} = \text{Ground}$ ,  $V_O = 1.4\text{ V}$ ,  $T_{\text{amb}} = 25\text{ }^{\circ}\text{C}$  (unless otherwise stated)

| Symbol                   | Parameter                            | Test conditions                                                                                                                                         | Min. | Typ.  | Max. | Unit                           |
|--------------------------|--------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|------|-------|------|--------------------------------|
| $V_{i0}$                 | Input offset voltage <sup>(1)</sup>  | $T_{\text{amb}} = 25\text{ }^{\circ}\text{C}$                                                                                                           |      | 2     | 7    | mV                             |
|                          |                                      | $T_{\text{min}} \leq T_{\text{amb}} \leq T_{\text{max}}$                                                                                                |      |       | 9    |                                |
| $\Delta V_{i0}/\Delta T$ | Input offset voltage drift           |                                                                                                                                                         |      | 7     | 30   | $\mu\text{V}/^{\circ}\text{C}$ |
| $I_{i0}$                 | Input offset current                 | $T_{\text{amb}} = 25\text{ }^{\circ}\text{C}$                                                                                                           |      | 2     | 30   | nA                             |
|                          |                                      | $T_{\text{min}} \leq T_{\text{amb}} \leq T_{\text{max}}$                                                                                                |      |       | 40   |                                |
| $DI_{i0}$                | Input offset current drift           |                                                                                                                                                         |      | 10    | 200  | $\text{pA}/^{\circ}\text{C}$   |
| $I_{ib}$                 | Input bias current <sup>(2)</sup>    | $T_{\text{amb}} = 25\text{ }^{\circ}\text{C}$                                                                                                           |      | 20    | 150  | nA                             |
|                          |                                      | $T_{\text{min}} \leq T_{\text{amb}} \leq T_{\text{max}}$                                                                                                |      |       | 300  |                                |
| $A_{vd}$                 | Large signal voltage gain            | $V_{CC+} = 15\text{ V}$ , $R_L = 2\text{ k}\Omega$ , $V_O = 1.4\text{ V}$ to $11.4\text{ V}$ , $T_{\text{amb}} = 25\text{ }^{\circ}\text{C}$            | 50   | 100   |      | V/mV                           |
|                          |                                      | $V_{CC+} = 15\text{ V}$ , $R_L = 2\text{ k}\Omega$ , $V_O = 1.4\text{ V}$ to $11.4\text{ V}$ , $T_{\text{min}} \leq T_{\text{amb}} \leq T_{\text{max}}$ | 25   |       |      |                                |
| SVR                      | Supply voltage rejection ratio       | $R_S \leq 10\text{ k}\Omega$ , $T_{\text{amb}} = 25\text{ }^{\circ}\text{C}$                                                                            | 65   | 110   |      | dB                             |
|                          |                                      | $R_S \leq 10\text{ k}\Omega$ , $T_{\text{min}} \leq T_{\text{amb}} \leq T_{\text{max}}$                                                                 | 65   |       |      |                                |
| $I_{CC}$                 | Supply current, all op amps, no load | $T_{\text{amb}} = 25\text{ }^{\circ}\text{C}$ , $V_{CC+} = 5\text{ V}$                                                                                  |      | 0.7   | 1.2  | mA                             |
|                          |                                      | $T_{\text{amb}} = 25\text{ }^{\circ}\text{C}$ , $V_{CC+} = 30\text{ V}$                                                                                 |      | 1.5   | 3    |                                |
|                          |                                      | $T_{\text{min}} \leq T_{\text{amb}} \leq T_{\text{max}}$ , $V_{CC+} = 5\text{ V}$                                                                       |      | 0.8   | 1.2  |                                |
|                          |                                      | $T_{\text{min}} \leq T_{\text{amb}} \leq T_{\text{max}}$ , $V_{CC+} = 30\text{ V}$                                                                      |      | 1.5   | 3    |                                |
| CMR                      | Common-mode rejection ratio          | $R_S \leq 10\text{ k}\Omega$ , $T_{\text{amb}} = 25\text{ }^{\circ}\text{C}$                                                                            | 70   | 80    |      | dB                             |
|                          |                                      | $R_S \leq 10\text{ k}\Omega$ , $T_{\text{min}} \leq T_{\text{amb}} \leq T_{\text{max}}$                                                                 | 60   |       |      |                                |
| $I_O$                    | Output short-circuit current         | $V_{id} = 1\text{ V}$ , $V_{CC+} = 15\text{ V}$ , $V_O = 2\text{ V}$                                                                                    | 20   | 40    | 70   | mA                             |
| $I_{\text{sink}}$        | Output sink current                  | $V_{id} = -1\text{ V}$ , $V_{CC+} = 15\text{ V}$ , $V_O = 2\text{ V}$                                                                                   | 10   | 20    |      |                                |
|                          |                                      | $V_{id} = -1\text{ V}$ , $V_{CC+} = 15\text{ V}$ , $V_O = 0.2\text{ V}$                                                                                 | 12   | 50    |      | $\mu\text{A}$                  |
| $V_{OH}$                 | High-level output voltage            | $V_{CC+} = 30\text{ V}$ , $R_L = 2\text{ k}\Omega$ , $T_{\text{amb}} = 25\text{ }^{\circ}\text{C}$                                                      | 26   | 27    |      | V                              |
|                          |                                      | $V_{CC+} = 30\text{ V}$ , $R_L = 2\text{ k}\Omega$ , $T_{\text{min}} \leq T_{\text{amb}} \leq T_{\text{max}}$                                           | 26   |       |      |                                |
|                          |                                      | $V_{CC+} = 30\text{ V}$ , $R_L = 10\text{ k}\Omega$ , $T_{\text{amb}} = 25\text{ }^{\circ}\text{C}$                                                     | 27   | 28    |      |                                |
|                          |                                      | $V_{CC+} = 30\text{ V}$ , $R_L = 10\text{ k}\Omega$ , $T_{\text{min}} \leq T_{\text{amb}} \leq T_{\text{max}}$                                          | 27   |       |      |                                |
|                          |                                      | $V_{CC+} = 5\text{ V}$ , $R_L = 2\text{ k}\Omega$ , $T_{\text{amb}} = 25\text{ }^{\circ}\text{C}$                                                       | 3    |       |      |                                |
|                          |                                      | $V_{CC+} = 5\text{ V}$ , $R_L = 2\text{ k}\Omega$ , $T_{\text{min}} \leq T_{\text{amb}} \leq T_{\text{max}}$                                            | 3.5  |       |      |                                |
| $V_{OL}$                 | Low-level output voltage             | $R_L = 10\text{ k}\Omega$ , $T_{\text{amb}} = 25\text{ }^{\circ}\text{C}$                                                                               |      | 5     | 20   | mV                             |
|                          |                                      | $R_L = 10\text{ k}\Omega$ , $T_{\text{min}} \leq T_{\text{amb}} \leq T_{\text{max}}$                                                                    |      |       | 20   |                                |
| SR                       | Slew rate                            | $V_{CC+} = 15\text{ V}$ , $V_{in} = 0.5\text{ to }3\text{ V}$ , $R_L = 2\text{ k}\Omega$ , $C_L = 100\text{ pF}$ , unity gain                           |      | 0.4   |      | $\text{V}/\mu\text{s}$         |
| GBP                      | Gain bandwidth product               | $V_{CC+} = 30\text{ V}$ , $V_{in} = 10\text{ mV}$ , $R_L = 2\text{ k}\Omega$ , $C_L = 100\text{ pF}$                                                    |      | 1.3   |      | MHz                            |
| THD                      | Total harmonic distortion            | $f = 1\text{ kHz}$ , $A_V = 20\text{ dB}$ , $R_L = 2\text{ k}\Omega$ , $V_O = 2\text{ V}_{pp}$ , $C_L = 100\text{ pF}$ , $V_{CC+} = 30\text{ V}$        |      | 0.015 |      | %                              |

# Electrical characteristics

LM2902

| Symbol          | Parameter                         | Test conditions                                                               | Min. | Typ. | Max. | Unit                         |
|-----------------|-----------------------------------|-------------------------------------------------------------------------------|------|------|------|------------------------------|
| $e_n$           | Equivalent input noise voltage    | $f = 1 \text{ kHz}$ , $R_S = 100 \text{ } \Omega$ , $V_{CC^+} = 30 \text{ V}$ |      | 40   |      | $\text{nV}/\sqrt{\text{Hz}}$ |
| $V_{O1}/V_{O2}$ | Channel separation <sup>(3)</sup> | $1 \text{ kHz} \leq f \leq 20 \text{ kHz}$                                    |      | 120  |      | dB                           |

## Notes:

<sup>(1)</sup> $V_O = 1.4 \text{ V}$ ,  $R_S = 0 \text{ } \Omega$ ,  $5 \text{ V} < V_{CC^+} < 30 \text{ V}$ ,  $0 \text{ V} < V_{ic} < (V_{CC^+}) - 1.5 \text{ V}$ .

<sup>(2)</sup>The direction of the input current is out of the IC. This current is essentially constant, independent of the state of the output, so there is no change in the load on the input lines.

<sup>(3)</sup>Due to the proximity of external components, ensure that stray capacitance does not cause coupling between these external parts. Typically, this can be detected as this type of capacitance increases at higher frequencies.

## 5 Electrical characteristic curves


Figure 3: Input bias current vs.  $T_{amb}$ 

Figure 4: Input voltage range




Figure 5: Current limiting




Figure 6: Supply current




Figure 7: Gain bandwidth product




Figure 8: Voltage follower pulse response




Figure 9: Common-mode rejection ratio




Figure 10: Output characteristics (sink)




Figure 11: Open-loop frequency response




Figure 12: Voltage follower pulse response




Figure 13: Large signal frequency response




Figure 14: Output characteristics (source)




Figure 15: Input current




Figure 16: Voltage gain




Figure 17: Power supply and common-mode rejection ratio





Figure 18: Large signal voltage gain



## 6 Typical single-supply applications

Figure 19: AC coupled inverting amplifier




Figure 20: AC coupled non-inverting amplifier




Figure 21: Non-inverting DC gain




Figure 22: DC summing amplifier




Figure 23: Active bandpass filter




Figure 24: High input Z adjustable gain DC instrumentation amplifier




Figure 25: High input Z, DC differential amplifier




Figure 26: Low drift peak detector





Figure 27: Using symmetrical amplifiers to reduce input current (general concept)



## 7 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: **[www.st.com](http://www.st.com)**. ECOPACK® is an ST trademark.

## 7.1 SO14 package information

Figure 28: SO14 package outline




Table 4: SO14 mechanical data

| Ref. | Dimensions  |      |      |        |      |       |
|------|-------------|------|------|--------|------|-------|
|      | Millimeters |      |      | Inches |      |       |
|      | Min.        | Typ. | Max. | Min.   | Typ. | Max.  |
| A    | 1.35        |      | 1.75 | 0.05   |      | 0.068 |
| A1   | 0.10        |      | 0.25 | 0.004  |      | 0.009 |
| A2   | 1.10        |      | 1.65 | 0.04   |      | 0.06  |
| B    | 0.33        |      | 0.51 | 0.01   |      | 0.02  |
| C    | 0.19        |      | 0.25 | 0.007  |      | 0.009 |
| D    | 8.55        |      | 8.75 | 0.33   |      | 0.34  |
| E    | 3.80        |      | 4.0  | 0.15   |      | 0.15  |
| e    |             | 1.27 |      |        | 0.05 |       |
| H    | 5.80        |      | 6.20 | 0.22   |      | 0.24  |
| h    | 0.25        |      | 0.50 | 0.009  |      | 0.02  |
| L    | 0.40        |      | 1.27 | 0.015  |      | 0.05  |
| k    | 8° (max)    |      |      |        |      |       |
| ddd  |             |      | 0.10 |        |      | 0.004 |

## 7.2 TSSOP14 package information

Figure 29: TSSOP14 package outline




Table 5: TSSOP14 mechanical data

| Ref. | Dimensions  |      |      |        |        |        |
|------|-------------|------|------|--------|--------|--------|
|      | Millimeters |      |      | Inches |        |        |
|      | Min.        | Typ. | Max. | Min.   | Typ.   | Max.   |
| A    |             |      | 1.20 |        |        | 0.047  |
| A1   | 0.05        |      | 0.15 | 0.002  | 0.004  | 0.006  |
| A2   | 0.80        | 1.00 | 1.05 | 0.031  | 0.039  | 0.041  |
| b    | 0.19        |      | 0.30 | 0.007  |        | 0.012  |
| c    | 0.09        |      | 0.20 | 0.004  |        | 0.0089 |
| D    | 4.90        | 5.00 | 5.10 | 0.193  | 0.197  | 0.201  |
| E    | 6.20        | 6.40 | 6.60 | 0.244  | 0.252  | 0.260  |
| E1   | 4.30        | 4.40 | 4.50 | 0.169  | 0.173  | 0.176  |
| e    |             | 0.65 |      |        | 0.0256 |        |
| L    | 0.45        | 0.60 | 0.75 | 0.018  | 0.024  | 0.030  |
| L1   |             | 1.00 |      |        | 0.039  |        |
| k    | 0°          |      | 8°   | 0°     |        | 8°     |
| aaa  |             |      | 0.10 |        |        | 0.004  |

### 7.3 QFN16 3x3 package information

Figure 30: QFN16 3x3 package outline





Table 6: QFN16 3x3 mechanical data

| Ref. | Dimensions  |      |      |        |       |       |
|------|-------------|------|------|--------|-------|-------|
|      | Millimeters |      |      | Inches |       |       |
|      | Min.        | Typ. | Max. | Min.   | Typ.  | Max.  |
| A    | 0.80        | 0.90 | 1.00 | 0.031  | 0.035 | 0.039 |
| A1   | 0           |      | 0.05 | 0      |       | 0.002 |
| A3   |             | 0.20 |      |        | 0.008 |       |
| b    | 0.18        |      | 0.30 | 0.007  |       | 0.012 |
| D    | 2.90        | 3.00 | 3.10 | 0.114  | 0.118 | 0.122 |
| D2   | 1.50        |      | 1.80 | 0.059  |       | 0.071 |
| E    | 2.90        | 3.00 | 3.10 | 0.114  | 0.118 | 0.122 |
| E2   | 1.50        |      | 1.80 | 0.059  |       | 0.071 |
| e    |             | 0.50 |      |        | 0.020 |       |
| L    | 0.30        |      | 0.50 | 0.012  |       | 0.020 |

Figure 31: QFN16 3x3 recommended footprint



## 8 Ordering information

Table 7: Order codes

| Order code               | Temperature range  | Package                         | Packing               | Marking |
|--------------------------|--------------------|---------------------------------|-----------------------|---------|
| LM2902D                  | -40 ° C to 125 ° C | SO14                            | Tube or tape and reel | 2902    |
| LM2902DT                 |                    |                                 |                       |         |
| LM2902PT                 |                    | TSSOP14                         | Tape and reel         | K5H     |
| LM2902Q4T                |                    | QFN16 3x3                       |                       |         |
| LM2902YDT <sup>(1)</sup> |                    | SO14, automotive grade level    |                       | 2902Y   |
| LM2902YPT <sup>(1)</sup> |                    | TSSOP14, automotive grade level |                       |         |

**Notes:**

<sup>(1)</sup>Qualified and characterized according to AEC Q100 and Q003 or equivalent, advanced screening according to AEC Q001 & Q002 or equivalent.

## 9 Revision history

**Table 8: Document revision history**

| Date        | Revision | Changes                                                                                                                                                                                                                                                                                                                                                                                                             |
|-------------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 30-Nov-2001 | 1        | Initial release.                                                                                                                                                                                                                                                                                                                                                                                                    |
| 01-Jul-2005 | 2        | PPAP references inserted in the datasheet, see Table 3: Order codes.<br>ESD protection inserted in Table 1 on page 4.                                                                                                                                                                                                                                                                                               |
| 31-Oct-2005 | 3        | An error in the device description was corrected on page 1.<br>PPAP reference inserted in the datasheet see Table 3: Order codes.<br>Minor grammatical and formatting changes throughout.                                                                                                                                                                                                                           |
| 18-Jun-2007 | 4        | Values for thermal resistance junction to ambient and ESD HBM corrected in Table 1: Absolute maximum ratings (AMR).<br>Values for thermal resistance junction to case added in Table 1: Absolute maximum ratings (AMR).<br>Table 2: Operating conditions added.<br>Electrical characteristics figure captions updated.<br>Section 6: Package information updated.<br>Table 3: Order codes moved to end of document. |
| 18-Dec-2007 | 5        | Removed power dissipation parameter from AMR table and added maximum junction temperature.<br>Updated footnotes for automotive grade order codes.<br>Updated format of package information.                                                                                                                                                                                                                         |
| 16-Feb-2012 | 6        | Added AMR values for input current in Table 1 on page 4.<br>Added QFN16 3 x 3 mm package information in Chapter 7: Ordering information.<br>Removed LM2902YD order code from Table 3 and changed status of LM2902YPT order code.                                                                                                                                                                                    |
| 29-Jan-2013 | 7        | Small text/layout changes in Features and Description.<br>Updated Figure 2: Pin connections (top view).<br>Table 3: $V_{CC+} = 5V$ , $V_{CC-} = \text{Ground}$ , $V_o = 1.4V$ , $T_{amb} = 25^{\circ}C$ (unless otherwise specified): $DV_{io}$ replaced by $DV_{io}/DT$ .<br>Replaced SO-14 package silhouette, package mechanical drawing (Figure 29) and package mechanical data (Table 5).                      |
| 11-Jan-2017 | 8        | Removed DIP package<br><a href="#">Figure 1: "Schematic diagram (1/4 LM2902)"</a> : removed two diodes<br><a href="#">Table 1: "Absolute maximum ratings (AMR)"</a> : updated value of $V_{CC}$<br>Updated TSSOP14 package for L and aaa parameters                                                                                                                                                                 |

**IMPORTANT NOTICE – PLEASE READ CAREFULLY**

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2017 STMicroelectronics – All rights reserved