


SKiIP25AC12T4V25



MiniSKiIP® 2

SKiIP25AC12T4V25

Features


- Trench 4 IGBT's
- Robust and soft freewheeling diodes in CAL technology
- Highly reliable spring contacts for electrical connections
- UL recognised file no. E63532

Typical Applications*

- Inverter up to 26 kVA
- Typical motor power 15 kW

Remarks

- V_{CEsat} , V_F = chip level value
- Case temp. limited to $T_C = 125^\circ\text{C}$ max. (for baseplateless modules $T_C = T_S$)
- product rel. results valid for $T_j \leq 150$ (recomm. $T_{op} = -40 \dots +150^\circ\text{C}$)
- Dynamic test results for $V_{cc} = 600\text{V}$, $R_{Gon/off} = 12\Omega$, $I_C = 50\text{A}$, $V_{GE} = \pm 15\text{V}$: $E_{on} = 5.6\text{mJ}$, $E_{off} = 6.1\text{mJ}$, $E_{rr} = 3.3\text{mJ}$, $di/dt_{on} = 1440\text{A}/\mu\text{s}$, $t_{don} = 58\text{ns}$, $t_r = 43\text{ns}$, $di/dt_{off} = 600\text{A}/\mu\text{s}$, $t_{doff} = 370\text{ns}$, $t_f = 65\text{ns}$




AC

Absolute Maximum Ratings				
Symbol	Conditions		Values	Unit
Inverter - IGBT				
V_{CES}	$T_j = 25^\circ\text{C}$		1200	V
I_C	$T_j = 175^\circ\text{C}$	$T_s = 25^\circ\text{C}$	69	A
		$T_s = 70^\circ\text{C}$	56	A
I_{Cnom}			50	A
I_{CRM}	$I_{CRM} = 3 \times I_{Cnom}$		150	A
V_{GES}			-20 ... 20	V
t_{psc}	$V_{CC} = 800\text{V}$	$T_j = 150^\circ\text{C}$	10	μs
	$V_{GE} \leq 15\text{V}$			
	$V_{CES} \leq 1200\text{V}$			
T_j			-40 ... 175	$^\circ\text{C}$
Inverse - Diode				
I_F	$T_j = 175^\circ\text{C}$	$T_s = 25^\circ\text{C}$	60	A
		$T_s = 70^\circ\text{C}$	48	A
I_{Fnom}			50	A
I_{FRM}	$I_{FRM} = 3 \times I_{Fnom}$		150	A
I_{FSM}	10 ms, sin 180°, $T_j = 150^\circ\text{C}$		270	A
T_j			-40 ... 175	$^\circ\text{C}$
Module				
$I_{t(RMS)}$	$T_{terminal} = 80^\circ\text{C}$, 20A per spring		60	A
T_{stg}			-40 ... 125	$^\circ\text{C}$
V_{isol}	AC sinus 50Hz, t = 1 min		2500	V

Characteristics						
Symbol	Conditions		min.	typ.	max.	Unit
Inverter - IGBT						
$V_{CE(sat)}$	$I_C = 50\text{A}$	$T_j = 25^\circ\text{C}$	1.85	2.10		V
		$T_j = 150^\circ\text{C}$	2.20	2.40		V
V_{CE0}		$T_j = 25^\circ\text{C}$	0.8	0.9		V
		$T_j = 150^\circ\text{C}$	0.7	0.8		V
r_{CE}	$V_{GE} = 15\text{V}$	$T_j = 25^\circ\text{C}$	21	24		m Ω
		$T_j = 150^\circ\text{C}$	30	32		m Ω
$V_{GE(th)}$	$V_{GE} = V_{CE}$, $I_C = 1.7\text{mA}$		5	5.8	6.5	V
I_{CES}	$V_{GE} = 0\text{V}$	$T_j = 25^\circ\text{C}$	0.1	0.3		mA
		$V_{CE} = 1200\text{V}$				mA
C_{ies}	$V_{CE} = 25\text{V}$	$f = 1\text{MHz}$	2.77			nF
C_{oes}		$f = 1\text{MHz}$	0.20			nF
C_{res}		$f = 1\text{MHz}$	0.16			nF
Q_G	- 8 V...+ 15 V		283			nC
R_{Gint}	$T_j = 25^\circ\text{C}$		4			Ω
$t_{d(on)}$	$V_{CC} = 800\text{V}$	$T_j = 150^\circ\text{C}$	45			ns
t_r	$I_C = 22\text{A}$	$T_j = 150^\circ\text{C}$	19			ns
		$T_j = 150^\circ\text{C}$	3.4			mJ
E_{on}	$R_{Gon} = 12\Omega$	$T_j = 150^\circ\text{C}$	3.4			mJ
$t_{d(off)}$	$R_{Goff} = 1\Omega$	$T_j = 150^\circ\text{C}$	480			ns
		$di/dt_{on} = 1640\text{A}/\mu\text{s}$				ns
t_f	$di/dt_{off} = 320\text{A}/\mu\text{s}$	$T_j = 150^\circ\text{C}$	44			ns
E_{off}	$V_{GE} = +15/0\text{V}$	$T_j = 150^\circ\text{C}$	3.1			mJ
$R_{th(j-s)}$	per IGBT		0.71			K/W

SKiIP25AC12T4V25



MiniSKiIP® 2

SKiIP25AC12T4V25

Features

- Trench 4 IGBT's
- Robust and soft freewheeling diodes in CAL technology
- Highly reliable spring contacts for electrical connections
- UL recognised file no. E63532


Typical Applications*

- Inverter up to 26 kVA
- Typical motor power 15 kW

Remarks

- V_{CEsat} , V_F = chip level value
- Case temp. limited to $T_C = 125^\circ\text{C}$ max. (for baseplateless modules $T_C = T_S$)
- product rel. results valid for $T_j \leq 150$ (recomm. $T_{op} = -40 \dots +150^\circ\text{C}$)
- Dynamic test results for $V_{cc} = 600\text{V}$, $R_{Gon/off} = 12\Omega$, $I_c = 50\text{A}$, $V_{GE} = \pm 15\text{V}$: $E_{on} = 5.6\text{mJ}$, $E_{off} = 6.1\text{mJ}$, $E_{rr} = 3.3\text{mJ}$, $di/dt_{on} = 1440\text{A}/\mu\text{s}$, $t_{don} = 58\text{ns}$, $t_r = 43\text{ns}$, $di/dt_{off} = 600\text{A}/\mu\text{s}$, $t_{doff} = 370\text{ns}$, $t_f = 65\text{ns}$

Characteristics						
Symbol	Conditions		min.	typ.	max.	Unit
Inverse - Diode						
$V_F = V_{EC}$	$I_F = 50\text{ A}$ $V_{GE} = 0\text{ V}$ chiplevel	$T_j = 25^\circ\text{C}$		2.2	2.5	V
		$T_j = 150^\circ\text{C}$		2.2	2.5	V
V_{F0}		$T_j = 25^\circ\text{C}$		1.3	1.5	V
		$T_j = 150^\circ\text{C}$		0.9	1.1	V
r_F		$T_j = 25^\circ\text{C}$		18	21	m Ω
		$T_j = 150^\circ\text{C}$		26	28	m Ω
I_{RRM}	$I_F = 22\text{ A}$	$T_j = 150^\circ\text{C}$		0		A
Q_{rr}	$di/dt_{off} = 1680\text{ A}/\mu\text{s}$	$T_j = 150^\circ\text{C}$		5.5		μC
E_{rr}	$V_{GE} = 0\text{ V}$	$T_j = 150^\circ\text{C}$		2.9		mJ
$R_{th(j-s)}$	$V_{CC} = 800\text{ V}$	$T_j = 150^\circ\text{C}$		0.95		K/W
	per Diode					
Module						
M_s	to heat sink		2		2.5	Nm
w				65		g
Temperatur Sensor						
R_{100}	$T_C = 100^\circ\text{C}$ ($R_{25} = 1000\Omega$)			1670 \pm 3%		Ω
$R(T)$	$R(T) = 1000\Omega [1 + A(T - 25^\circ\text{C}) + B(T - 25^\circ\text{C})^2]$], $A = 7.635 \cdot 10^{-3} \text{ }^\circ\text{C}^{-1}$, $B = 1.731 \cdot 10^{-5} \text{ }^\circ\text{C}^{-2}$					



AC




Fig. 1: Typ. output characteristic, inclusive $R_{CC'+EE'}$




Fig. 2: Rated current vs. temperature $I_C = f(T_S)$




Fig. 3: Typ. turn-on /-off energy = $f(I_C)$




Fig. 4: Typ. turn-on /-off energy = $f(R_G)$




Fig. 5: Typ. transfer characteristic




Fig. 6: Typ. gate charge characteristic




Fig. 7: Typ. switching times vs. I_C




Fig. 8: Typ. switching times vs. gate resistor R_G




Fig. 9: Transient thermal impedance of IGBT and Diode




Fig. 10: CAL diode forward characteristic




Fig. 11: Typ. CAL diode peak reverse recovery current




Fig. 12: Typ. CAL diode recovery charge

