


### PRODUCT FEATURES

- Low Forward Voltage
- High Surge Current Capability
- Low Leakage Current
- Low Inductance Package

### APPLICATIONS

- Field Supply For DC Motors
- Line Rectifiers For Transistorized AC Motor Controllers
- Non-controllable Rectifiers For AC/DC Converter



### Module Type

| Module Type | $V_{RRM}$<br>(Repetitive Peak Reverse Voltage) | $V_{RSM}$<br>(Non-Repetitive Peak Reverse Voltage) | Unit |
|-------------|--|--|------|
| MMD100F200X | 2000   | 2100   | V    |

### ABSOLUTE MAXIMUM RATINGS

$T_C = 25^\circ\text{C}$  unless otherwise specified

| Symbol        | Parameter/Test Conditions            |   | Values      | Unit              |      |
|---------------|--------------------------------------|---|-------------|-------------------|------|
| $I_D$         | Output Current(D.C.)                 | Three phase, half wave, $T_C = 95^\circ\text{C}$      | 100         | A                 |      |
| $I_{FSM}$     | Non Repetitive Surge Forward Current | 1/2 cycle, 50Hz, peak value, $T_C = 45^\circ\text{C}$ | 1000        |                   |      |
|               |                                      | 1/2 cycle, 60Hz, peak value, $T_C = 45^\circ\text{C}$ | 1100        |                   |      |
| $I^2t$        | For Fusing                           | 1/2 cycle, 50Hz, peak value, $T_C = 45^\circ\text{C}$ | 5.0         | KA <sup>2</sup> S |      |
|               |                                      | 1/2 cycle, 60Hz peak value, $T_C = 45^\circ\text{C}$  | 5.1         |                   |      |
| $P_D$         | Power Dissipation                    |   | 830         | W                 |      |
| $T_J$         | Junction Temperature                 |   | -40 to +150 | $^\circ\text{C}$  |      |
| $T_{STG}$     | Storage Temperature Range            |   | -40 to +125 | $^\circ\text{C}$  |      |
| $V_{ISO}$     | Isolation Breakdown Voltage          | AC, 50Hz(R.M.S), t=1minute                            | 3000        | V                 |      |
| <b>Torque</b> | Module to Sink                       | Recommended (M6)                                      | 3~5         | Nm                |      |
| <b>Torque</b> | Module Electrodes                    | Recommended (M6)                                      | 3~5         | Nm                |      |
| $R_{thJC}$    | Junction to Case Thermal Resistance  |   | per diode   | 0.9               | K /W |
|               |                                      |   | per module  | 0.15              |      |
| <b>Weight</b> |                                      |   | 250         | g                 |      |

## ELECTRICAL CHARACTERISTICS

$T_C = 25^\circ\text{C}$  unless otherwise specified

| Symbol   | Parameter/Test Conditions                                   | Min.                                     | Typ. | Max. | Unit       |
|----------|---|--|------|------|------------|
| $I_{RM}$ | Maximum Reverse Leakage Current                             |  |      | 1    | mA         |
|          |   | $V_R = V_{RRM}, T_J = 125^\circ\text{C}$ |      | 10   |            |
| $V_F$    | Forward Voltage Drop  |  |      | 1.35 | V          |
| $V_{TO}$ | For power loss calculations only, $T_J = 125^\circ\text{C}$ |  |      | 0.86 | V          |
| $r_T$    |   |  |      | 4.9  | m $\Omega$ |




Figure 1. Forward Voltage Drop vs Output Current




Figure 2. Power dissipation vs Output Current




Figure 3. Max Non Repetitive Forward Surge Current




Figure 4. Output current vs Case temperature





Figure 5. Transient Thermal Impedance



Dimensions in (mm)  
Figure 6. Package Outline