


PRODUCT FEATURES

- Ultrafast Recovery Time
- Soft Recovery Characteristics
- Low Recovery Loss
- Low Forward Voltage
- High Surge Current Capability
- Low Leakage Current



APPLICATIONS

- Inversion Welder
- Uninterruptible Power Supply
- Plating Power Supply
- Ultrasonic Cleaner and Welder
- Converter & Chopper
- PFC



ABSOLUTE MAXIMUM RATINGS

$T_C = -25^\circ\text{C}$ unless otherwise specified

Symbol	Parameter/Test Conditions		Values	Unit
V_R	Maximum D.C. Reverse Voltage		400	V
V_{RRM}	Maximum Repetitive Reverse Voltage			
$I_{F(AV)}$	Average Forward Current	$T_C = 80^\circ\text{C}$, Per Diode	400	A
$I_{F(RMS)}$	RMS Forward Current	$T_C = 80^\circ\text{C}$, Per Diode	560	
I_{FSM}	Non Repetitive Surge Forward Current	$T_J = 45^\circ\text{C}$, $t = 10\text{ms}$, Sine, peak value	2800	
		$T_J = 45^\circ\text{C}$, $t = 8.3\text{ms}$, Sine, peak value	3080	
I^2t	For Fusing	$T_J = 45^\circ\text{C}$, $t = 10\text{ms}$, Sine, peak value	39.2	KA ² S
		$T_J = 45^\circ\text{C}$, $t = 8.3\text{ms}$, Sine, peak value	39.3	
P_D	Power Dissipation		1250	W
T_J	Junction Temperature		-40 to +150	$^\circ\text{C}$
T_{STG}	Storage Temperature Range		-40 to +125	$^\circ\text{C}$
V_{isol}	Isolation Breakdown Voltage	AC, 50Hz(R.M.S), $t = 1\text{minute}$	3000	V
Torque	Module to Sink	Recommended (M6)	3~5	Nm
	Module Electrodes	Recommended (M6)	3~5	Nm
R_{thJC}	Junction to Case Thermal Resistance(Per Diode)		0.1	$^\circ\text{C} / \text{W}$
Weight			160	g

ELECTRICAL CHARACTERISTICS

T_C = 25°C unless otherwise specified

Symbol	Parameter/Test Conditions		Min.	Typ.	Max.	Unit
I_{RM}	Maximum Reverse Leakage Current	V _R = 400V			1	mA
		V _R = 400V, T _J = 125°C			10	
V_F	Forward Voltage	I _F = 400A		1.6	2.0	V
		I _F = 400A, T _J = 125°C		1.35		
t_{rr}	Reverse Recovery Time (I _F = 1A, di _F /dt = -200A/μs, V _R = 30V)			50		ns
t_{rr}	Reverse Recovery Time	I _F = 400A, V _R = 200V,		110		ns
I_{RRM}	Maximum Reverse Recovery Current	di _F /dt = -200A/μs		16		A
t_{rr}	Reverse Recovery Time	I _F = 400A, V _R = 200V,		210		ns
I_{RRM}	Maximum Reverse Recovery Current	di _F /dt = -200A/μs, T _J = 125°C		26		A




Figure 1. Forward Voltage Drop vs Forward Current




Figure 2. Reverse Recovery Time vs di_F/dt




Figure 3. Reverse Recovery Current vs di_F/dt




Figure 4. Reverse Recovery Charge vs di_F/dt




Figure 5. Forward current vs Case temperature





Figure 6. Transient Thermal Impedance



Dimensions in (mm)
Figure 7. Package Outline