

2SK3596-01L,S,SJ

FUJI POWER MOSFET

Super FAP-G Series

N-CHANNEL SILICON POWER MOSFET

■ Features

High speed switching
Low on-resistance
No secondary breakdown
Low driving power
Avalanche-proof

■ Applications

Switching regulators
UPS (Uninterruptible Power Supply)
DC-DC converters

■ Maximum ratings and characteristic Absolute maximum ratings

● (Tc=25°C unless otherwise specified)

Item	Symbol	Ratings	Unit
Drain-source voltage	V _{DS}	200	V
	V _{DSX} *5	170	V
Continuous drain current	I _D	±30	A
Pulsed drain current	I _{D(puls)}	±120	A
Gate-source voltage	V _{GS}	±30	V
Non-repetitive Avalanche current	I _{AS} *2	30	A
Maximum Avalanche Energy	E _{AS} *1	387	mJ
Maximum Drain-Source dV/dt	dV _{DS} /dt *4	20	kV/μs
Peak Diode Recovery dV/dt	dV/dt *3	5	kV/μs
Max. power dissipation	P _D	Ta=25°C	1.67
		Tc=25°C	135
Operating and storage temperature range	T _{ch}	+150	°C
	T _{stg}	-55 to +150	°C

*1 L=689μH, V_{CC}=48V *2 T_{ch}≤150°C *3 I_F=-I_D, -di/dt=50A/μs, V_{CC}≤BV_{DSS}, T_{ch}≤150°C

*4 V_{DS} ≤ 200V *5 V_{GS}=-30V


● Electrical characteristics (Tc =25°C unless otherwise specified)

Item	Symbol	Test Conditions	Min.	Typ.	Max.	Units
Drain-source breakdown voltage	V _{(BR)DSS}	I _D = 250μA V _{GS} =0V	200			V
Gate threshold voltage	V _{GS(th)}	I _D = 250μA V _{DS} =V _{GS}	3.0		5.0	V
Zero gate voltage drain current	I _{DSS}	V _{DS} =200V V _{GS} =0V			25	μA
		V _{DS} =160V V _{GS} =0V			250	μA
Gate-source leakage current	I _{GSS}	V _{GS} =±30V V _{DS} =0V		10	100	nA
Drain-source on-state resistance	R _{DS(on)}	I _D =15A V _{GS} =10V		50	66	mΩ
Forward transconductance	g _{fs}	I _D =15A V _{DS} =25V	12.5	25		S
Input capacitance	C _{iss}	V _{DS} =75V		1960	2940	pF
Output capacitance	C _{oss}	V _{GS} =0V		260	390	pF
Reverse transfer capacitance	C _{rss}	f=1MHz		18	27	pF
Turn-on time t _{on}	td(on)	V _{CC} =48V I _D =15A		20	30	ns
	t _r	V _{GS} =10V		17	26	ns
Turn-off time t _{off}	td(off)	R _{GS} =10 Ω		53	80	ns
	t _f			19	29	ns
Total Gate Charge	Q _G	V _{CC} =100V		51	76.5	nC
Gate-Source Charge	Q _{GS}	I _D =30A		15	22.5	nC
Gate-Drain Charge	Q _{GD}	V _{GS} =10V		16	24	nC
Avalanche capability	I _{AV}	L=100μH T _{ch} =25°C	30			A
Diode forward on-voltage	V _{SD}	I _F =30A V _{GS} =0V T _{ch} =25°C		1.10	1.65	V
Reverse recovery time	t _{rr}	I _F =30A V _{GS} =0V		0.19		μs
Reverse recovery charge	Q _{rr}	-di/dt=100A/μs T _{ch} =25°C		1.4		μC


● Thermal characteristics

Item	Symbol	Test Conditions	Min.	Typ.	Max.	Units
Thermal resistance	R _{th(ch-c)}	channel to case			0.926	°C/W
	R _{th(ch-a)}	channel to ambient			75.0	°C/W







■ Outline Drawings (mm)











■ Equivalent circuit schematic






Characteristics







Outline Drawings (mm)



Note: 1. Guaranteed mark of avalanche ruggedness.